



BSPP Female Fixed Cap

10,000 PSI / 689 bar / 68.9 MPa*

Dimensions & variants

Dimensions in mm

Item number	BSPP Thread	A	Hex
9851040431610K	G 1/4"	20	22
9851060631610K	G 3/8"	23	24
9851080831610K	G 1/2"	28	32
9851121231610K	G 3/4"	30	41
9851161631610K	G 1"	33	50

Article number: 9851 | 12 | 12 | 316 | 10K

Series | BSPP thread code | BSPP thread code | Material |
Pressure class

Product specifications

Connection — BSPP Female Fixed	Configuration	General product information
BSPP Female Fixed ISO 1179-2 sealing interface Connection: ISO 1179-2 Thread: ISO 228-1	Cap One threaded port Sizes: see dimensions	Material: AISI 316L EN 1.4404 / UNS S31603 Working pressure: 10,000 PSI* 689 bar / 68.9 MPa* HS code: 73079900 Country of origin: Norway

Technical info

BSPP Female Fixed side: Fixed parallel G thread to ISO 1179-2 / ISO 228-1. Cap configuration for closing a mating BSPP male connection.

* The stated working pressure is based on Intermec's established design calculations, dimensional design criteria and more than 35 years of experience with high-pressure fittings in demanding offshore and oil & gas applications. Suitability depends on correct installation, mating connection, material and operating conditions.