


PRODUCT GROUP
9950
10K

MATERIAL
SS316L
Stainless steel



NPT Female Cap

10,000 PSI / 689 bar / 68.9 MPa*

Dimensions & variants

Dimensions in mm

Item number	NPT Female	A	Hex
9950040431610K	1/4"NPT	24	22
9950060631610K	3/8"NPT	26	24
9950080831610K	1/2"NPT	32	32
9950121231610K	3/4"NPT	34	41
9950161631610K	1"NPT	38	50

Article number: 9950 | 12 | 12 | 316 | 10K

Series | NPT thread code | NPT thread code | Material |
Pressure class

Product specifications

Connection — NPT Female	Configuration	General product information
NPT Female Tapered pipe thread Thread: ASME B1.20.1	Cap One threaded port Sizes: see dimensions	Material: AISI 316L EN 1.4404 / UNS S31603 Working pressure: 10,000 PSI* 689 bar / 68.9 MPa* HS code: 73079900 Country of origin: Norway

Technical info

NPT female side: Tapered pipe thread to ASME B1.20.1. Cap configuration for closing a mating NPT male connection.

* The stated working pressure is based on Intermec's established design calculations, dimensional design criteria and more than 35 years of experience with high-pressure fittings in demanding offshore and oil & gas applications. Suitability depends on correct installation, mating connection, material and operating conditions.