


PRODUCT GROUP

**MP-NAV
20K**

MATERIAL

SS316L

Stainless steel



Medium Pressure Nut Anti-Vibration

20,000 PSI / 1,379 bar / 137.9 MPa*

Dimensions & variants

Dimensions in mm

Item number	MP Size	A	Hex
MP04NAV316	1/4" (04)	14	17
MP06NAV316	3/8" (06)	14	22
MP09NAV316	9/16" (09)	14	24
MP12NAV316	3/4" (12)	23	32
MP16NAV316	1" (16)	26	38
MP24NAV316	1 1/2" (24)	29	55

Article number: MP | 04 | NAV | 316

Series | MP size code | Anti-vibration nut | Material

Product specifications

Component — Anti-vibration nut

Medium Pressure anti-vibration nut
Sizes: see dimensions
MP size: see dimensions

Assembly

Medium Pressure cone-and-thread
For use with MP-GAV and MP-SAV

General product information

Material: AISI 316L
EN 1.4404 / UNS S31603
Working pressure: 20,000 PSI*
1,379 bar / 137.9 MPa*
HS code: 73079900
Country of origin: Norway

Technical info

For use with MP-GAV and MP-SAV. Dimensionally compatible with the established 20,000 psi Medium Pressure cone-and-thread connection geometry.

* The stated working pressure is based on Intermec's established design calculations, dimensional design criteria and more than 35 years of experience with high-pressure fittings in demanding offshore and oil & gas applications. Suitability depends on correct installation, mating connection, material and operating conditions.